




LD1085CXX

3 A low-drop, adjustable positive voltage regulator

Features

- Typical dropout 1.3 V (at 3 A)
- Three terminal adjustable output voltage
- Guaranteed output current up to 3 A
- Output tolerance $\pm 2\%$ at 25 °C and $\pm 3\%$ in full temperature range
- Internal power and thermal limit
- Wide operating temperature range -40 °C to 125 °C
- Package available: DPAK
- Pinout compatibility with standard adjustable VREG



Description

The LD1085C is a low drop voltage regulator able to provide up to 3 A of output current. Dropout is guaranteed at a maximum of 1.5 V at the maximum output current, decreasing at lower loads. The LD1085C is pin to pin compatible with the older 3-terminal adjustable regulators, but has better performances in term of drop and output tolerance.

A 2.85 V output version is suitable for SCSI-2 active termination. Unlike PNP regulators, where a part of the output current is wasted as quiescent current, the LD1085C quiescent current flows into the load, so increase efficiency. Only a 10 μ F minimum capacitor is need for stability.

The device is supplied in DPAK. On chip trimming allows the regulator to reach a very tight output voltage tolerance, within $\pm 2\%$ at 25 °C.

Table 1. Device summary

| Order codes | Packages |
|-------------|----------------------|
| LD1085CDT-R | DPAK (tape and reel) |

Contents

1 **Diagram 3**

2 **Pin configuration 4**

3 **Maximum ratings 5**

4 **Schematic application 6**

5 **Electrical characteristics 7**


6 **Typical application 8**

7 **Package mechanical data 12**

8 **Revision history 15**


1 Diagram

Figure 1. Schematic diagram



2 Pin configuration

Figure 2. Pin connections (top view)



3 Maximum ratings

Table 2. Absolute maximum ratings

| Symbol | Parameter | Value | Unit |
|-----------|--------------------------------------|--------------------|------|
| V_I | DC input voltage | 30 | V |
| I_O | Output current | Internally limited | |
| P_D | Power dissipation | Internally limited | |
| T_{STG} | Storage temperature range | -55 to +150 | °C |
| T_{OP} | Operating junction temperature range | -40 to +125 | °C |


Note: Absolute maximum ratings are those values beyond which damage to the device may occur. Functional operation under these condition is not implied.

Table 3. Thermal data

| Symbol | Parameter | DPAK | Unit |
|------------|-------------------------------------|------|------|
| R_{thJC} | Thermal resistance junction-case | 3 | °C/W |
| R_{thJA} | Thermal resistance junction-ambient | 62.5 | °C/W |

4 Schematic application

Figure 3. Application circuit



5 Electrical characteristics

Table 4. Electrical characteristics of LD1085CDT
($V_I = 4.25\text{ V}$, $C_I = C_O = 10\text{ }\mu\text{F}$, $T_A = -40\text{ to }125\text{ }^\circ\text{C}$, unless otherwise specified).

| Symbol | Parameter | Test condition | Min. | Typ. | Max. | Unit |
|------------------|--|--|-------|-------|-------|---------------|
| V_O | Output voltage ⁽¹⁾ | $I_O = 10\text{mA}$, $T_J = 25^\circ\text{C}$ | 1.225 | 1.25 | 1.275 | V |
| | | $I_O = 10\text{mA}$ to 3A , $V_I = 2.85\text{ to }30\text{V}$ ⁽¹⁾ | 1.213 | 1.25 | 1.288 | V |
| ΔV_O | Line regulation | $I_O = 10\text{mA}$, $V_I = 2.85\text{ to }16.5\text{V}$, $T_J = 25^\circ\text{C}$ | | 0.015 | 0.2 | % |
| | | $I_O = 10\text{mA}$, $V_I = 2.85\text{ to }16.5\text{V}$ | | 0.035 | 0.2 | % |
| ΔV_O | Load regulation | $I_O = 10\text{mA}$ to 5A , $T_J = 25^\circ\text{C}$ | | 0.1 | 0.3 | % |
| | | $I_O = 0\text{ to }5\text{A}$ | | 0.2 | 0.4 | % |
| V_d | Dropout voltage | $I_O = 5\text{A}$ | | 1.3 | 1.5 | V |
| $I_{O(\min)}$ | Minimum load current | $V_I = 30\text{V}$ | | 3 | 10 | mA |
| I_{sc} | Short circuit current | $V_I - V_O = 5\text{V}$ | 3.2 | 4.5 | | A |
| | | $V_I - V_O = 25\text{V}$ | 0.2 | 0.5 | | A |
| | Thermal regulation | $T_A = 25^\circ\text{C}$, 30ms pulse | | 0.003 | 0.015 | %/W |
| SVR | Supply voltage rejection | $f = 120\text{ Hz}$, $C_O = 25\mu\text{F}$, $C_{ADJ} = 25\text{ }\mu\text{F}$, $I_O = 3\text{A}$, $V_I = 6.25 \pm 3\text{V}$ | 60 | 75 | | dB |
| I_{ADJ} | Adjust pin current | $V_I = 4.25\text{V}$, $I_O = 10\text{ mA}$ | | 55 | 120 | μA |
| ΔI_{ADJ} | Adjust pin current change | $I_O = 10\text{mA}$ to 3A , $V_I = 2.75\text{ to }16.5\text{V}$ ⁽¹⁾ | | 0.2 | 5 | μA |
| eN | RMS output noise voltage (% of V_O) | $T_A = 25^\circ\text{C}$, $f = 10\text{Hz to }10\text{kHz}$ | | 0.003 | | % |
| S | Temperature stability | | | 0.5 | | % |
| S | Long term stability | $T_A = 125^\circ\text{C}$, 1000Hrs | | 0.5 | | % |

1. See short-circuit current curve for available output current at fixed dropout.

6 Typical application

(Unless otherwise specified $T_J = 25^\circ\text{C}$, $C_I = C_O = 10\ \mu\text{F}$)

Figure 4. Output voltage vs temperature




Figure 5. Output voltage vs temperature




Figure 6. Output voltage vs temperature




Figure 7. Short circuit current vs dropout voltage




Figure 8. Line regulation vs temperature




Figure 9. Load regulation vs temperature




Figure 10. Dropout voltage vs temperature




Figure 11. Dropout voltage vs output current




Figure 12. Adjust pin current vs temperature




Figure 13. Quiescent current vs temperature




Figure 14. Line regulation vs temperature




Figure 15. Supply voltage rejection vs output current




Figure 16. Supply voltage rejection vs frequency




Figure 17. Supply voltage rejection vs temperature




Figure 18. Minimum load current vs temperature




Figure 19. Stability




Figure 20. Stability




Figure 21. Line transient




Figure 22. Line transient




Figure 23. Load transient





Figure 24. Load transient




7 Package mechanical data

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a lead-free second level interconnect. The category of second Level Interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com.

DPAK mechanical data


| Dim. | mm. | | | inch. | | |
|------|------|------|------|-------|-------|-------|
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 2.2 | | 2.4 | 0.086 | | 0.094 |
| A1 | 0.9 | | 1.1 | 0.035 | | 0.043 |
| A2 | 0.03 | | 0.23 | 0.001 | | 0.009 |
| B | 0.64 | | 0.9 | 0.025 | | 0.035 |
| b4 | 5.2 | | 5.4 | 0.204 | | 0.212 |
| C | 0.45 | | 0.6 | 0.017 | | 0.023 |
| C2 | 0.48 | | 0.6 | 0.019 | | 0.023 |
| D | 6 | | 6.2 | 0.236 | | 0.244 |
| D1 | | 5.1 | | | 0.200 | |
| E | 6.4 | | 6.6 | 0.252 | | 0.260 |
| E1 | | 4.7 | | | 0.185 | |
| e | | 2.28 | | | 0.090 | |
| e1 | 4.4 | | 4.6 | 0.173 | | 0.181 |
| H | 9.35 | | 10.1 | 0.368 | | 0.397 |
| L | 1 | | | 0.039 | | |
| (L1) | | 2.8 | | | 0.110 | |
| L2 | | 0.8 | | | 0.031 | |
| L4 | 0.6 | | 1 | 0.023 | | 0.039 |
| R | | 0.2 | | | 0.008 | |
| V2 | 0° | | 8° | 0° | | 8° |



0068772-F

Tape & reel DPAK-PPAK mechanical data

| Dim. | mm. | | | inch. | | |
|------|-------|-------|-------|-------|-------|--------|
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | | | 330 | | | 12.992 |
| C | 12.8 | 13.0 | 13.2 | 0.504 | 0.512 | 0.519 |
| D | 20.2 | | | 0.795 | | |
| N | 60 | | | 2.362 | | |
| T | | | 22.4 | | | 0.882 |
| Ao | 6.80 | 6.90 | 7.00 | 0.268 | 0.272 | 0.276 |
| Bo | 10.40 | 10.50 | 10.60 | 0.409 | 0.413 | 0.417 |
| Ko | 2.55 | 2.65 | 2.75 | 0.100 | 0.104 | 0.105 |
| Po | 3.9 | 4.0 | 4.1 | 0.153 | 0.157 | 0.161 |
| P | 7.9 | 8.0 | 8.1 | 0.311 | 0.315 | 0.319 |



8 Revision history

Table 5. Document revision history

| Date | Revision | Changes |
|-------------|----------|---|
| 07-Oct-2004 | 6 | Mistake in Table 1. |
| 03-Jul-2007 | 7 | Order codes updated. |
| 09-Apr-2008 | 8 | Modified: Table 1 on page 1 . |

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2008 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com